



| Ø16 1.8/16mm C | | |
|---------------------------|------------|-------------------------------|
| FOCAL LENGTH | | f=16mm |
| MAX. DIAMETER (RATIO) | | F=1:1.8~22 |
| ELEMENT | | 9 GROUPS 11 ELEMENTS |
| PICTURE SIZE | | 12.8x9.6mm |
| ANGLE | VER. ANGLE | 33.6° |
| | HOR. ANGLE | 44.0° |
| | DIA. ANGLE | 53.8° |
| DISTORTION (TV) | | 0.02% |
| SHOOTING RANGE AT | VER. | 69.9 mm |
| MINIMUM FOCUS | HOR. | 93.5 mm |
| DISTANCE | DIA. | 117 mm |
| MINIMUM FOCUS DISTANCE | | 0.1m |
| FLANGE BACK | | 17.526mm in air |
| BACK FOCUS | | 13.0mm in air |
| FILTER SCREW SIZE | | M34x0.5 |
| FRONT/REAR EFFECTIVE DIA. | | FRONT Ø27mm REAR Ø16.5mm |
| MOUNT | | C-MOUNT |
| EXIT PUPIL | | -26.2mm |
| TEMPERATURE RANGE | | -10~+50° C |
| STORAGE TEMPERATURE RANGE | | -20~+60° C |
| RESOLUTION CENTER/CORNER | | CENTER 160L/mm CORNER 120L/mm |
| LENS COATING | | WIDE BAND MULTI COATING |
| WEIGHT | | g |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | | | |
|----------|-------|----------------|-----|--------|----|--------|----|
| | | 尺 度 | 1/1 | 承 認 | 八木 | 製 図 | 大口 |
| | | LM16SC | | | | | |
| | | 1" F1.8 f=16mm | | | | | |
| 2013.5.8 | 作成年月日 | | | | | | |